NODHA

Orbital Pipe Cutting Machine

X & SCISSOR Pipe Orbital Cutting Machine

The orbital pipe cutting machine is designed for cutting and beveling of thin-walled stainless steel, mainly used in food, pharmaceutical, semi-conductor, daily chemical and other fields. The cut end face is vertical without burrs and can be directly welded. With the function of beveling can also be completed by using a bevel saw blade to ensure the welding quality when required.

NODHA introduce the second generation technology to provide more options according to different applications. With a option of brushless motors 1300W and 1500W, the customized 1500W motor provides more powerful power and is suitable for the cutting of thicker wall stainless steel pipes.





Features

Compact design with light weight Cold cutting/beveling improve safety Vertical incision, burr-free end surface Multi-point clamping to avoid deformation Quick saw blade change Anti-winding cables are provided Second saw balde postion to cutoff elbows or Tee



Powerful Motor





Pa

UB UB UB



ED1500

Cutting Saw Blade

ED1300

	Part No.	Specification				Wall Thickness		
		OD(mm)	Qty of Teeth	ID(mm)	Thk(mm)	mm	Inch	
L	6364	63	64	16	1.6	1.0-2.5	0.039-0.098	
L	63100	63	100	16	1.2	0.7-1.5	0.0276-0.059	
L	6844	68	44	16	1.8	2.0-7.0	0.079-0.276	
L	6872	68	72	16	1.6	1.0-2.5	0.039-0.098	
L	8034	80	34	16	2	5.0-12.0	0.197-0.47	
L	8044	80	44	16	1.8	5.0-10.0	0.197-0.394	
L	8054	80	54	16	1.8	2.0-7.0	0.079-0.276	
L	8080	80	80	16	1.8	1.0-2.5	0.039-0.098	

Tool Life reference: Complete 423 cut-off by L6844 work for 304 S.S. Dia.50.8x2mm thk

www.nodha.com



Specification

art No.	ED1300	ED1500		
ower Supply	220-230V 1PH 50/60HZ			
ower	1300W	1500W		
able length	2.8M	5.3M		
peed adjustable	Yes	Yes		
/eight	4.8 kgs	5.5kgs		

Beveling Saw Blade

art No.	Beveling Angle	Application	
B30	30°	х	
B37.5	37.5°	^	
B30R	30°	SCISSOR	
B37.5R	37.5°	501350K	





NODHA

X Pipe Orbital Cutting Machine



Features

Durable cast iron body, aluminium clamping
Two evitting court black position increases the evitting concetty
Two cutting saw blade position improve the cutting capacity
Square and burr-free cutting
Simple manual cutter head rotation
Deformation free aluminium contact elemning overam
Deformation free aluminium contact clamping system
Mechanical fixed length is more durable
Swivel cord increase security
Deveryful hwychlana water fer gytting waat waterial
Powerful brushless motor for cutting most material

Twin motor handle makes operation safe and easier

Specifications

Model	Х3	X4	
Dia - OD	6-76.2 mm	12-120 mm	
Pipe OD	0.236-3 inch	0.472-4.724 in	
	≤ 8 mm	≤ 8 mm	
Wall thickness	≤ 0.315 inch	≤ 0.315 inch	
Motor	ED1500		
Power Supply	220-230V 1PH 50/60HZ		
Motor Power	1500W	1500W	
Saw Blade RPM	88-212	88-212	
Net Weight	38.5 kgs	50 kgs	
Shipping Weight	52 kgs	65 kgs	
Package	Ply wood case		
Packing size	560*520*400mm	630*520*480	





5





Standard Supply

X Pipe Cuttting machine
Saw blade - 3 pcs
Quick Mounting plate
Hand tool set
Operation Manual
Transport plywood case

www.nodha.com

NODHA

SCISSOR Pipe Orbital Cutting Machine







Features

Integrated design, all rotating parts are concentrated in the body
Deformation free stainless steel self-centering clamping system
Two cutting saw blade position improve the cutting capacity
Two cutting saw blade position improve the cutting capacity
Square and burr-free cutting
Manual feed module makes operate more easlier
With the function of forward and reverse rotation functions
Four or six clamping pads makes clamping more stable
Four or six clamping paus makes clamping more stable
Powerful motor for cutting most material thicker pipe
Swivel cord increase security



Specifications


Model	SCISSOR 3		SCISSOR 4		SCISSOR 6	
Order Code	CB3M	CB3M Pro	CB4M	CB4M Pro	CB6M	CB6M Pro
Pipe OD	6 - 80 mm		12 - 120 mm		16 - 171 mm	
Pipe OD	0.236 - 3.15 inch		0.472 - 4.724 inch		0.63 - 6.73 inch	
Wall thickness	≤ 5mm	≤ 8mm	≤ 5mm	≤ 8mm	≤ 5mm	≤ 8mm
waii thickness	≤ 0.197 inch	≤ 0.315 inch	≤ 0.197 inch	≤ 0.315 inch	≤ 0.197 inch	≤ 0.315 inch
Motor	ED1300	ED1500	ED1300	ED1500	ED1300	ED1500
Power Supply	220-230V 1PH 50/60HZ					
Motor Power	1300W	1500W	1300W	1500W	1300W	1500W
Saw Blade RPM	90-270	95-230	90-270	95-230	90-270	150-250
Clamping jaws	Clamping jaws		4			
Net Weight	31 kgs	32 kgs	40 kgs	41 kgs	55 kgs	56 kgs
Shipping Weight	44 kgs	45 kgs	53 kgs	54 kgs	70 kgs	71 kgs
Package	Package		Ply wood case			
Packing size	620*460*550mm		640*490*580mm		690*540*630mm	

Model	SCISS	SCISSOR		
Order Code	CB8M	CB8M Pro	CB12M	C
Dine OD	55 - 22	140 - 330		
Pipe OD	2.165 - 8.9	5.512 - 12.99		
Wall thickness	≤ 5mm	≤ 8mm	≤ 5mm	
waii unickness	≤ 0.197 inch	≤ 0.315 inch	≤ 0.197 inch	≤
Motor	ED1300	ED1500	ED1300	
Power Supply		H 50/60HZ		
Motor Power	1300W	1500W	1300W	
Saw Blade RPM	90-270	95-230	90-270	
Clamping jaws		6	;	
Net Weight	60 kgs	61 kgs	81 kgs	
Shipping Weight	78 kgs	79 kgs	105 kgs	
Package	Ply wood case			
Packing size	750*600*	850*700*7		

5



R 12



Standard Supply

SCISSOR Pipe Cuttting machine
Saw blade - 3 pcs
Hand tool set
Operation Manual