

GMMA-60S

Portable Edge Milling Machine

Features

Bevel angle adjustable	Digital display
Feed speed adjustable	24V control box, more safe
OL protection(Feed QF)	Auto clamping
Dense teeth Cutter Head	Standard milling inserts

Specification


Power Supply	AC 380V 50HZ
Total Power	4520W
Spindle Speed	1050r/min
Feed Speed	0~1500mm/min
Plate Thickness	6~60mm
Plate Width	>80mm
Processing Length	>300mm
Bevel Angle	0°~60°Adjustable
Single pass Bevel Width	0~20mm
Bevel Width	0~45mm
Cutter Dia.	Φ63mm
Cutter Qty	6pcs
Worktable Height	700~760mm
Travel Space	800*800mm
Net Weight	200kg
Gross Weight	255kg
Package Size	840*740*1250mm



Performance parameter & Bevel Type

4.52kwh Energy Consumption **400W** Feed Motor **24V** Control Box Voltage

Ra3.2~6.3 Surface **0°~60°** Bevel Angle **45mm** Max.Bevel Width



a	15°	30°	37.5°	45°	60°
w	45mm	45mm	45mm	45mm	40mm

! Bevel angle " Bevel width

Application



GMMA-60R

Double-sided Edge Milling Machine

Features

Bevel angle adjustable	Digital display
Feed speed adjustable	24V control box, more safe
OL protection(Feed QF)	Auto clamping
Dense teeth Cutter Head	Standard milling inserts

Specification

Power Supply	AC 380V 50HZ
Total Power	3400W
Spindle Speed	1050r/min
Feed Speed	0~1500mm/min
Plate Thickness	6~60mm
Plate Width	>80mm
Processing Length	>300mm
Bevel Angle	±10°~60°Adjustable
Single pass Bevel Width	0~20mm
Bevel Width	0~55mm
Cutter Dia.	Φ63mm
Cutter Qty	6pcs
Worktable Height	730~760mm
Travel Space	800*800mm
Net Weight	245kg
Gross Weight	300kg
Package Size	860*1100*1500mm



Performance parameter & Bevel Type

3.4kwh Energy Consumption **400W** Feed Motor **24V** Control Box Voltage

Ra3.2~6.3 Surface **10°~60°** Bevel Angle **55mm** Max.Bevel Width



a	10°	30°	37.5°	45°	60°
w	40mm	52mm	53mm	55mm	43mm

! Bevel angle " Bevel width

Application

